## 硬化、回火、碳氮共渗连续式炉

## **Conveyer Belt Furnace for Hardening, Tempering, and Carbonitriding**





カロ ハバノコ エイ	TAHAM (XXIVALIENT)				
	• 燃气加热				
优点	• 均温度优良(±5℃)				
	• 在加热室能自动控温和显示				
	氧含量				
	• 可依客户需求,提供炉内不同				
	的充入气体和环境				
	• 特殊保温节省能源消耗				
	• 提供高纯度的气体环境,并减				
	少气体消耗				
其他选项	• 上料和下料装置				
	• 称重和定量给料系统				
	• 硬化炉或回火炉				
	<ul><li></li></ul>				
	• 油分离机和离心机				
	• 淬火和抛光槽				
	• 控制和监视系统				
使用于	• 表面硬化				
	<ul><li>碳氮共渗</li></ul>				
	<ul><li>硬化</li></ul>				
	• 淬油、淬火、聚合物淬火或盐				
	浴淬火				
-	·				

• 电加热 (热风循环)

加热方式



## 硬化、回火、碳氮共渗连续式炉

## **Conveyer Belt Furnace for Hardening, Tempering, and Carbonitriding**







Heating	Electric Heating (convection)
Method	Gas Heating
Advantage	<ul> <li>Temperature Uniformity         (±5°C)</li> <li>Automatic temperature         control and oxygen content in         the chamber</li> <li>Accommodate reactive or         insert gas atmospheres upon         customer's request</li> <li>Energy efficient design         insulation</li> <li>Ultra-pure atmospheric         environment with minimal gas         consumption</li> </ul>
Option	System for the loading and the handling of the material Weighing and dosing systems Hardening furnaces and tempering furnaces Belt or screw washing machines Oil separators and centrifuges Quenching and burnishing tanks Control and supervision system
Application	<ul> <li>Casehardening</li> <li>Carbonitriding</li> <li>Hardening</li> <li>Tempering</li> <li>Quenching in oil, water, polymer and salt</li> </ul>